



UR1200A

UR1200A, an **A**ctive RFID Reader, which is developed and produced by Microprogram, is built-in short range activator, combo trigger and read function. UR1200A is small and lightweight, can be installed on each corner easily. UR1200A provides RS-485 interface, supports most application, makes the existing system with wireless sensing ability.

Spec

UHF Frequency	922 MHz ~ 928 MHz, NCC
UHF Antenna Pattern	Omni
UHF Range (Reader - Tag)	100 meter for Free space
LF Frequency	125KHz
LF Range (Activator - Tag)	up to 4 meter for Free space
Dimensions	85 x 128 x 33 mm
Weight	156g (with antenna)
Mounting	Wall-mounted
Operating Temperature, Humidity	0°C ~ +85°C, 10%~100% RH
Storage Temperature, Humidity	-40°C ~ +85°C, 10%~100% RH
Case Material	ABS+PC
I/O Interface	RS232 / RS485 / Wiegand 26, 34
Input Power (Adaptor)	DC12~24V
Power	3W
Warranty	1 year

Add
14F., No.262, Sec. 2,
Henan Rd., Xitun Dist.,
Taichung City 407,
Taiwan (R.O.C.)

Tel
+886-4-2369-2699

Fax
+886-4-2451-8100

Mail
sales@program.com.tw

Web
www.program.com.tw

